# SODIMM DDR3 PC3-8500 1066MHz

## Features

- Fully PC3-8500 Compliant
- JEDEC-Standard 204-pin Small Outline Dual Inline Memory Module (SODIMM)
- Unbuffered
- Cas Latency 7
- Power Supply: 1.5 V ± 0.2 V
- Pure Power and Ground Planes
- Gold PCB connector

## Ordering Information

| | DENSITY | REFERENCE | EAN |
|---|---|---|---|
| *Optima* | 2GB | SODI102GBN/8500/3-BX | 3536401462378 |
| *Optima* | Kit 4GB (2x2GB) | K-SODI4GBN/8500/3-BX | 3536401002628 |
| *Optima* | 4GB | SODI104GBN/8500/3-BX | 3536401462804 |
| | | | |
| *Premium* | 2GB | S2GBN16Q1066E-SB | 3536401462392 |
| *Premium* | Kit 4GB (2x2GB) | KS4GBN16Q1066E-SB | 3536401002635 |
| *Premium* | 4GB | S4GBN16M1066E-SB | 3536401462811 |

Some of our capacities are also available in Premium packagings for distribution and integration purposes.

Optima packaging

Premium packaging

## Not sure of your memory needs ?

**Try our online configurator !**

PNY.EU

Product and specifications discussed here in are for evaluation and reference purpose only and are subject to change by PNY Technologies without notice.

**For more information, visit : WWW.PNY.EU**

PNY Technologies Europe - RCS Bordeaux B394790430. PNY, PNY Technologies and the PNY logo are registered trademarks of PNY Technologies Inc. All other trademarks and logos are the property of their respective companies. Copyright ©2009 PNY Technologies, Inc. All rights reserved.